


## Fachadas Ventiladas com painéis Viroc - Estrutura de Aço Galvanizado


Parafusos e rebites para fixação dos painéis Viroc

Painéis de 12 mm de espessura


### DRILLNOX STAR TB 5.5x50 W16



### STARZAC/2C 5.5x38 W16




### Rebite AL/In A2 N.E 4.8x18 CEL16 e RIVCOLOR AL/In N.E 4.8x18 CEL




Acessório: Riveter Nose, utilização obrigatória

Painéis de 16mm de espessura


DRILLNOX STAR TB 5.5x50 W16



STARZAC/2C 6.3x50 W16



Rebite AL/In A2 N.E 4.8x22 CEL16 e RIVCOLOR AL/In N.E 4.8x22 CEL



Acessório: Riveter Nose, utilização obrigatória


Riveter Nose



RIVETER NOSE			
For riveter	Thread length.	Pack.	Code
<b>ACCUBIRD</b>	8	1	611 111
<b>LR 5 - LR 20</b>	13	1	611 110

Estrutura de suporte

Esquadros



USTB 3316  
USTB 3194

SEISMIC C1  
SEISMIC C2

Z450 galvanized SG 220 GD steel  
2.5 mm thickness

Z450 galvanized SG 220 GD steel  
2.5 mm thickness

**ISOLCO 3000 P2 M8/Ga**  
**Opening 9x20**

**ISOLCO 3000 P2 M10/Ga**  
**Opening 11x20**

L	Pack.	Code	Pack.	Code
40	200	367 100	200	367 130
50	200	367 101	200	367 131
60	200	367 102	200	367 132
70	200	367 103	200	367 133
80	200	367 104	200	367 134
90	200	367 105	200	367 135
100	100	367 106	100	367 136
110	100	367 107	100	367 137
120	100	367 108	100	367 138
130	100	367 109	100	367 139
140	100	367 110	100	367 140
150	100	367 111	100	367 141
160	100	367 112	100	367 142
170	100	367 113	100	367 143
180	100	367 114	100	367 144
190	100	367 115	100	367 145
200	50	367 116	50	367 146
210	50	367 117	50	367 147
220	50	367 118	50	367 148
230	50	367 119	50	367 149
240	50	367 120	50	367 150
250	50	367 121	50	367 151
260	50	367 122	50	367 152
270	50	367 123	50	367 153
280	50	367 124	50	367 154
290	50	367 125	50	367 155
300	50	367 126	50	367 156

Ancoragem (esquadro-suporte)

MARCOVIS FM-X5 TH 13 10/15x85, (1 un/esquadro)



							Polyamide PA6 + Screw in Carbon steel class 5.8 zinc plated $\geq 5 \mu\text{m}$	
							<b>MARCOVIS FM-X5 TH 13</b>	
$\emptyset$ / t <sub>tr</sub> x l	d	Screw l <sub>s</sub>	d <sub>0</sub>	h <sub>1</sub>	Pack.	Code		
10 / 15 x 85	/	90	10	80	Bucket 300	360 601		

Parafusos (esquadro-perfil)



Fastovis TH/Zn 5.5x25, (2 un/esquadro)



						Bare screw Carbon steel <b>FASTOVIS TH / Zn</b>	
CP	$\emptyset$ x L	Ref.	CS min	CA max.	H	Pack.	Code
1.5 to 4	5,5 x 25	4PI	-	11	8	500	284 900
1.5 to 4	5,5 x 25	4PI	-	11	8	100	284 902

Bucha plástica (isolamento-suporte)

INCO Black



• Load: Up to 17 Kg



Black polypropylene

**INCO Black**

$\emptyset$ / $t_{fix}$ x $l$	$d_0^{\#}$	$h_1$	Pack.	Code
8 / 40 x 60	8	30	500	358 101
8 / 60 x 80	8	30	500	358 102
8 / 80 x 100	8	30	500	358 104
8 / 100 x 120	8	30	250	358 105
<hr/>				
10 / 40 x 70	10	40	500	358 170
10 / 60 x 90	10	40	500	358 172
10 / 80 x 110	10	40	250	358 174
10 / 110 x 140	10	40	200	358 176

Chave centradora, ML 1000



**DRILL CENTRING TOOL  
ML 1000**

Model	Pack.	Code
Centring tool ML 1000	1	284 000

### Perfis auxiliar de angulo



Pre-painted Aluminium 1 mm thickness		
P.A.S. Al / PrL		
For panel thick. (mm)	Pack. (m) *	Code
10	30	611 700
15	30	611 702
20	30	611 704

(\*) Packaging: One 10 x 3 meters bundle, cannot be split

- Colours std.: RAL 1013 / 1015 / 7016 / 7035 / 9001 / 9007 / 9010 / 9016 - RAL Painting and other widths available on request
- Facade application:
  - Decorative corner profile




Pre-painted Aluminium 1 mm thickness		
P.A.R. Al / PrL		
For panel thick. (mm)	Pack. (m) *	Code
10	30	611 710
15	30	611 712
20	30	611 714

(\*) Packaging: One 10 x 3 meters bundle, cannot be split


- Colours std.: RAL 1013 / 1015 / 7016 / 7035 / 9001 / 9007 / 9010 / 9016 - RAL Painting and other widths available on request
- Facade application:
  - Decorative corner profile

### Placa de angulo



Galvanized steel Z 450 2.5 mm thickness		CORNER PLATE	
Ht	L	Pack.	Code
120	180	25	367 240

Perfil anti-roedores



		Galvanized carbon steel	
		RODENT-PROOF GRILLE / Ga	
A	B	Pack.	Code
30	40	1	666 377
30	50	1	666 376
30	60	1	666 375
30	70	1	666 374
30	80	1	666 373
30	90	1	666 372
30	100	1	666 371
30	110	1	666 370
30	120	1	666 369
30	130	1	666 368
30	140	1	666 367
30	150	1	666 366
30	160	1	666 365
30	170	1	666 364
30	180	1	666 363
30	190	1	666 362
30	200	1	666 361
30	210	1	666 360
30	220	1	666 359
30	230	1	666 358
30	240	1	666 357
30	250	1	666 356
30	260	1	666 355



Contactos para informação e fornecimento

Portugal

Tel: +351 912 110 413

Email : [pedro.durao.etanco@gmail.com](mailto:pedro.durao.etanco@gmail.com)

França

UK

Tel :+33 01 34 80 52 08

Tel :+44 179 256 19 11

Email : [export@etanco.fr](mailto:export@etanco.fr)

Email : [commercial.france@etanco.fr](mailto:commercial.france@etanco.fr)

Etanco Bélgica

Etanco Alemanha

Tel : +32 3 354 15 00

Tel : +49 27 39 47 99 64

Etanco Polónia

Etanco Roménia

Itália

Tel : + 48 55 24 22 926

Tel : +40 31 425 12 82

Tel :+39 04 327 479 11

Tel : +40 72 264 69 44

Tel :+39 02 990 480 62