Fachadas ventiladas con paneles Viroc - Estructura de Acero Galvanizado

Tornillos y remaches para la fijación de paneles Viroc

Paneles de 12 mm de espesor

SX3/15-L12-S16-5.5x32



Application
Stainless steel fastening of steel / aluminium sheet or façade panels to steel or aluminium structure in one operation: drilling, thread forming and sealing.





Product code	article number	VD	KL	d x L	PU	notes
SX3/15-L12-S16/1-5,5X32	1403191	3	15	5,5X32	250	

SX3/15-D16-5,5x30

Application
Stainless steel fastening of steel / aluminium sheet or façade panels to steel or aluminium structure in one operation: drilling, thread forming and sealing.



Product code	article number	VD	KL	d x L	PU	notes
SX3/15-D12-5,5X30	1403193	3	15	5,5X30	250	
SX3/15-D16-5,5X30	1270106	3	15	5,5X30	250	

Remaches AP16-S-5.0x21



Accesorio: Nosepiece (uso obligatorio)

Paneles de 16 mm de espesor

SX5-L12-S16-5.5x41



Remaches SS0-D15-5x22



Accesorio: Nosepiece (uso obligatorio)

Estructura de soporte

Escuadras

		B	50-T		
Application	Product	Type	L	KL	Application range
	■ Carbon steel	B	50-T		Fixed width A of 50 mm Length L. variable from 5 0 to 300 mm Fixed height H of 60 mm 8.5x30 mm and 8.5xL mm slot holes Holes dia Ø 6.5
		B	60-T		
		B	70-T		
		B	80-T		
		B	90-T		
		B	100-T		
		B	110-T		
		B	120-T		
		B	130-T		
		B	140-T		
		B	150-T		
		B	160-T		
		B	170-T		
		B	180-T		
		B	190-T		
		B	200-T		
		B	210-T		
		B	220-T		
		B	230-T		
		B	240-T		
		B	250-T		
		B	260-T		
		B	270-T		
		B	280-T		
		B	290-T		
		B	300-T		



Anclaje (escuadras-soporte)

FUR-10,0x80-SS (1 un/escuadra)

Application	Product	Approval	Order code FUR- 8,0x 80-SS: Type	d	L	t_{fix}	h_2	Application range
	■ Carbon steel	CE	FUR-	8,0x	80-SS	**10**	**90**	Anchoring depth h_{nom} min. 70 mm embedment  Drill bit for concrete: Ø 8mm: SDS4–Plus–8xL Ø 10mm: SDS4–Plus–10xL
			FUR-	8,0x	100-SS	**30**	**110**	
			FUR-	8,0x	120-SS	**50**	**130**	
			FUR-	10,0x	80-SS	**10**	**90**	
			FUR-	10,0x	100-SS	**30**	**110**	
			FUR-	10,0x	115-SS	**45**	**125**	
			FUR-	10,0x	135-SS	**65**	**145**	
			FUR-	10,0x	160-SS	**90**	**170**	
			FUR-	10,0x	185-SS	**115**	**195**	
			FUR-	10,0x	200-SS	**130**	**210**	
			FUR-	10,0x	230-SS	**160**	**240**	

Tornillos (escuadra-perfil de acero)

SD 5-5,5x25 (2 un/escuadra)

Application	Product	Approval	Order code SD 5- H15- 5,5x 22: Type	VD	HD	d	L	KL	Application range
	■ Carbon steel	CSTB	SD	5-		5,5x	25	**12**	VD max. steel: 5,0 mm t min. steel: 1,5 mm Assembly recommendations: 2 x SD5-5,5x25 for normal hole

Anclaje plástico (aislamiento-suporte)



d diameter | **L** overall length | **SD** Setting depth | **All measures in mm**

Applications	Product	Order code MDH- 8,0x 60 Type	d	L	SD	Application range
	● Plastic	MDH- 8,0x 60			**20**	
		MDH- 8,0x 80			**20**	
		MDH- 8,0x 100			**20**	
		MDH- 8,0x 120			**20**	
		MDH- 8,0x 140			**20**	
		MDH- 8,0x 160			**20**	
		MDH- 8,0x 180*			**30**	
		MDH- 8,0x 200*			**30**	
		MDH- 8,0x 220*			**30**	
		MDH- 8,0x 240*			**30**	

* two pieces

1. Drill a pilot hole
2. Set plug until head lies flush on insulation
3. Use a hammer for installation
4. MDH has to be hammered precisely onto insulation

Accesorios

Chave E420 tornillos de cabeza irius.

Nosepiece, Limitador de apriete de remaches

Centrador de furos para remaches

d diameter | **L** Length | **f** flute length | **t** thickness of structure | **All measures in mm**

Example order code		
DG-	**146x20**	**7,0**
Type	L	Nose
DG-	146x20-	7,0
DG-	146x20-	8,0
DG-	146x20-	9,0
DG-	146x20-	10,0

Application range



Can be used with all cordless screw drivers available on the market.

Llave para centrar tornillos con diámetro de 5,5 mm, ZL-SX/SD-5.5/8.0

Llave para centrar agujeros con diámetro de 5,1 mm, ZL-5.1/7-18

Perfil angular, auxiliar

PFS-K-Aluminium

Application	Product	PFS-K-A- 10/10 Type	axb	KL	Application range
	▲ Aluminium	PFS-K-A-	10/10	≤ **10**	Length of the profile: L = 2,8 m Thickness: e = 0,8 mm
		PFS-K-A-	18/18	≤ **18**	
		PFS-K-A-	29/29	≤ **29**	
		PFS-K-A-	40/40	≤ **40**	



PFS-Q-Aluminium

Application	Product	PFS-Q-A- 10/10 Type	axb	KL	Application range
	▲ Aluminium	PFS-Q-A-	10/10	≤ **10**	Length of the profile: L = 2,8 m Thickness: e = 0,8 mm
		PFS-Q-A-	18/18	≤ **18**	



PFR-Aluminium

Application	Product	PFR-A- 10/10 Type	axb	KL	Application range
	▲ Aluminium	PFR-A-	10/10	≤ **10**	Length of the profile: L = 2,8 m Thickness: e = 0,8 mm
		PFR-A-	15/15	≤ **15**	
		PFR-A-	18/18	≤ **18**	



Perfiles anti-roedores

PV-Aluminium

		PV-A- 30x30			
Application	Product	Type	hxl	KL	Application range
	▲ Aluminium	PV-A-	30x30		Length of the profile: L = 2,5 m Thickness: e = 0,8 mm 
		PV-A-	30x40		
		PV-A-	30x50		
		PV-A-	30x60		
		PV-A-	30x70		
		PV-A	30x90		
		PV-A-	40x100		
		PV-A-	40x120		
		PV-A-	40x140		
		PV-A-	40x160		
		PV-A-	40x180		
		PV-A-	40x200		
		PV-A-	40x220		
		PV-A-	40x240		
		PV-A-	40x260		
		PV-A-	40x280		
		PV-A-	40x300		

Contactos para información y subministro:

España

Jordi Casulleras

T +34 946 33 31 20 M +34 609 00 59 01

jorge.casulleras@sfs.com, es.sfs.com

Francia

T: +33 4 75 75 44 22

E: fr.info@sfs.com

UK

T: +44 (0) 330 0555 888

E: ukenquiries@sfs.com

USA

T: +1 610 376 5751

E: us.construction@sfs.com

Canadá

T: +1 905 847 5400

E: ca.info@sfs.com

Norway

T: +47 67 92 14 40

E: no.info@sfs.com

Sweden

T: +46 152 71 50 00

E: se.info@sfs.com

Finland

T: +358 9 3154 9810

E: fi.info@sfs.com

Nederland

T: +31 492 597 414

E: bnl.info@sfs.com

Polnad

T: +48 61 660 49 00

E: pl.info@sfs.com

Italy

T: +39 0434 995 1

E: it.info@sfs.com

Germany

T: +49 6171 700 20

E: de.info@sfs.com

Czech Republic

T: +420 481 354 4111

E: cz.construction@sfs.com

Estonia

T: +372 6610 600

E : ee.info@sfs.com