Fachadas Ventiladas com painéis Viroc - Estrutura de Madeira

Parafusos para fixação dos painéis Viroc

Painéis de 12 mm de espessura

TW-S-D16-4.8x38 W16



TW-S-D12-S16-4.8x38



Painéis de 16 mm de espessura

TW-S-D12-S16-4.8x44



TW-S-D12-S16-4.8x60



Estrutura de suporte

Esquadros

		B	50-T		
Application	Product	Type	L	KL	Application range
	■ Carbon steel	B	50-T		Fixed width A of 50 mm Length L. variable from 5 0 to 300 mm Fixed height H of 60 mm 8.5x30 mm and 8.5xL mm slot holes Holes dia Ø 6.5 
		B	60-T		
		B	70-T		
		B	80-T		
		B	90-T		
		B	100-T		
		B	110-T		
		B	120-T		
		B	130-T		
		B	140-T		
		B	150-T		
		B	160-T		
		B	170-T		
		B	180-T		
		B	190-T		
		B	200-T		
		B	210-T		
		B	220-T		
		B	230-T		
		B	240-T		
		B	250-T		
		B	260-T		
		B	270-T		
		B	280-T		
		B	290-T		
		B	300-T		

Ancoragem (esquadro-suporte)

FUR-10,0x80-SS (1 un/esquadro)

Application	Product	Approval	Order code FUR-	8,0x	80-SS	t_{fix}	h_2	Application range
	■ Carbon steel	CE	Type	d	L			
			FUR-	8,0x	80-SS	**10**	**90**	Anchoring depth h_{nom} min. 70 mm embedment
			FUR-	8,0x	100-SS	**30**	**110**	
			FUR-	8,0x	120-SS	**50**	**130**	
			FUR-	10,0x	80-SS	**10**	**90**	
			FUR-	10,0x	100-SS	**30**	**110**	
			FUR-	10,0x	115-SS	**45**	**125**	
			FUR-	10,0x	135-SS	**65**	**145**	
			FUR-	10,0x	160-SS	**90**	**170**	
			FUR-	10,0x	185-SS	**115**	**195**	
			FUR-	10,0x	200-SS	**130**	**210**	
			FUR-	10,0x	230-SS	**160**	**240**	



Drill bit for concrete:
Ø 8mm: SDS4–Plus–8xL
Ø 10mm: SDS4–Plus–10xL

Parafusos (esquadro-barrote)

SW-T-4,8x35 (3 un/esquadro) ou

SW3-T-H15-6,5x50 (2 un/esquadro)

Application	Product	Approval	Order code SW-T-	HD	4,8x d	35 L	KL	Application range
	■ Carbon steel	CSTB	SW-T-		4,8x	35		VD max. steel: 1 x1,0 mm 3 x0,75 mm Assembly recommendations: 3 x SW-T-4,8x35 for long hole Ø 6,5 mm
	■ Carbon steel	CSTB	SW3-T-	H15-	6,5x	50		 VD max. steel: 2 x1,25 mm Assembly recommendations: 1 x SW3-T-H15-6,5x50 for long hole 1 x SW-T-4,8x35 for normal hole

Banda EPDM



Product code	article number	d x L	PU	notes
EPDM-TAPE-0,75X60X25000	1122506	0,75X60X25 M	1	
EPDM-TAPE-0,75X80X25000	1193862	0,75X80X25 M	1	
EPDM-TAPE-0,75X100X25000	1122504	0,75X100X25 M	1	
EPDM-TAPE-0,75X120X25000	1288745	0,75X120X25 M	1	
EPDM-TAPE-1,2X70X25000	1379293	1,2X70X25 M	1	
EPDM-TAPE-1,2X120X25000	1379294	1,2X120X25 M	1	
EPDM-TAPE-ADHESIVE-0,75X60X25000	1122507	0,75X60X25 M	1	
EPDM-TAPE-ADHESIVE-0,75X100X25000	1122508	0,75X100X25 M	1	
EPDM-TAPE-ADHESIVE-0,75X120X25000	1329007	0,75X120X25 M	1	
EPDM-TAPE-ADHESIVE-1,2X110X25000	1386718	1,2X110X25 M	1	

Bucha plástica (isolamento-suporte)



d diameter | **L** overall length | **SD** Setting depth | **All measures in mm**

Applications	Product	Order code MDH- 8,0x 60 Type	d	L	SD	Application range
	● Plastic	MDH-	8,0x	60	**20**	 
		MDH-	8,0x	80	**20**	
		MDH-	8,0x	100	**20**	
		MDH-	8,0x	120	**20**	
		MDH-	8,0x	140	**20**	
		MDH-	8,0x	160	**20**	
		MDH-	8,0x	180*	**30**	 
		MDH-	8,0x	200*	**30**	
		MDH-	8,0x	220*	**30**	
		MDH-	8,0x	240*	**30**	

* two pieces

1. Drill a pilot hole
2. Set plug until head lies flush on insulation
3. Use a hammer for installation
4. MDH has to be hammered precisely onto insulation

Acessórios

Chave para centrar parafusos com diâmetro 4,8mm, ZL-SLA-4,8/7

Perfil auxiliar de angulo

PFS-K-Aluminium

Application	Product	PFS-K-A- 10/10 Type	axb	KL	Application range
	▲ Aluminium	PFS-K-A-	10/10	≤ **10**	Length of the profile: L = 2,8 m Thickness: e = 0,8 mm
		PFS-K-A-	18/18	≤ **18**	
		PFS-K-A-	29/29	≤ **29**	
		PFS-K-A-	40/40	≤ **40**	



PFS-Q-Aluminium

Application	Product	PFS-Q-A- 10/10 Type	axb	KL	Application range
	▲ Aluminium	PFS-Q-A-	10/10	≤ **10**	Length of the profile: L = 2,8 m Thickness: e = 0,8 mm
		PFS-Q-A-	18/18	≤ **18**	



PFR-Aluminium

Application	Product	PFR-A- 10/10 Type	axb	KL	Application range
	▲ Aluminium	PFR-A-	10/10	≤ **10**	Length of the profile: L = 2,8 m Thickness: e = 0,8 mm
		PFR-A-	15/15	≤ **15**	
		PFR-A-	18/18	≤ **18**	



Perfil anti-roedores

PV-Aluminium

		PV-A-	30x30		
Application	Product	Type	hxl	KL	Application range
	▲ Aluminium	PV-A-	30x30		Length of the profile: L = 2,5 m Thickness: e = 0,8 mm 
		PV-A-	30x40		
		PV-A-	30x50		
		PV-A-	30x60		
		PV-A-	30x70		
		PV-A	30x90		
		PV-A-	40x100		
		PV-A-	40x120		
		PV-A-	40x140		
		PV-A-	40x160		
		PV-A-	40x180		
		PV-A-	40x200		
		PV-A-	40x220		
		PV-A-	40x240		
		PV-A-	40x260		
		PV-A-	40x280		
		PV-A-	40x300		

Contactos para informação e fornecimento:

Portugal / Espanha

Jordi Casulleras

T +34 946 33 31 20 M +34 609 00 59 01

jorge.casulleras@sfs.com, es.sfs.com

France

T: +33 4 75 75 44 22

E: fr.info@sfs.com

UK

T: +44 (0) 330 0555 888

E: ukenquiries@sfs.com

USA

T: +1 610 376 5751

E: us.construction@sfs.com

Canada

T: +1 905 847 5400

E: ca.info@sfs.com

Norway

T: +47 67 92 14 40

E: no.info@sfs.com

Sweden

T: +46 152 71 50 00

E: se.info@sfs.com

Finland

T: +358 9 3154 9810

E: fi.info@sfs.com

Nederland

T: +31 492 597 414

E: bnl.info@sfs.com

Polnad

T: +48 61 660 49 00

E: pl.info@sfs.com

Italy

T: +39 0434 995 1

E: it.info@sfs.com

Germany

T: +49 6171 700 20

E: de.info@sfs.com

Czech Republic

T: +420 481 354 4111

E: cz.construction@sfs.com

Estonia

T: +372 6610 600

E : ee.info@sfs.com